



Cello W2202S 22" Full HD LED Monitor with speakers

- 22" LED display
- Full HD resolution 1920 x 1080 pixels
- Integrated speakers
- Contrast ratio 4000:1 from the darkest blacks to the brightest whites for a more dynamic viewing experience
- Flicker free display to reduce eye fatigue
- 16.7 million display colours delivering greater colour depth
- Low blue light to help protect your eyes and keep them more comfortable during prolonged use
- HDMI, VGA and earphone connections

Product Description:

This Cello 22" LED monitor is elegantly designed for use in an office or home environment. The Full HD display delivers 16.7 million colours for greater colour depth as well as high dynamic contrast at 4000:1. For prolonged use, the operators eyes are protected and comforted via the flicker free display and its low blue light output.

This Cello monitor also includes built-in speakers for added convenience and ease-of-use. The product comes complete with VGA cable and power cord.

	EAN	5060062268508
Panel Specifications	Size	21.5" diagonal
	Panel	FHD VA
	Display scale	16:9
	Backlight	ELED edge Type
	Maximum resolution	1920 x 1080
	Best working resolution	1920 x 1080 @ 60Hz
	Pixel Pitch	0.24825mm (H) x 0.24825mm (V)
	Active Area	476.64mm x 268.11mm
	Viewing angle	H:178°,V:178° CR>1000
	Center Luminance of White	Min:200cd/m ² ; Typ:250cd/m ²
	Contrast ratio	Typ:4000:1
	Response time	Typ:6.5ms
	Display Colours	16.7 M
	Colour Gaunt	Typ:72%

Display resolution	Input Signal	Mode	Resolution	Refresh rate	
	VGA	VGA		640 x 480	60HZ
		SVGA		800 x 600	60HZ
		XGA		1024 x 768	60HZ
		SXGA		1280 x 1024	60HZ
		WXGA		1440 x 900	60HZ
		WUXGA		1920 x 1080	60HZ

Interface configuration	Input Interface	HDMI	1
		VGA	1
	Output Interface	Earphone	1

Structure size	Base	Base	BCE2-24
		Elevation adjustment	Supported
	Size:	Product size(without base)	501 x 298 x 31.6mm (Thinnest:8.5mm)
		Product size(with base)	501 x 361 x 130mm
		Packing size	565 x 106 x 445mm
Weight	With BCE2-24: Net weight 2.3 Kg: Gross weight: 3.5 Kg		

Power management	Power (DC Power Adapter)	DC 12V/3A
	Working consumption	≤36W
	Standby consumption	≤0.5W
	Speaker	2 x 2W

Special Functions	Flicker Free	Supported
	Low blue light	Supported

Safety & Certification	Authentication		CE
	Environment	Working condition	Temperature: 5°C~40°C humidity: 10%~85% atmosphere: 86kPa~104kPa
		Storage condition	Temperature: -20°C~55°C humidity: 5%~95% atmosphere: 86kPa~104kPa

Accessory	LED Monitor	1PCS
	Base	1PCS
	Instructions	1PCS
	VGA Cable	1PCS
	Power Adapter	1PCS