



### Cello W2402S 24" Full HD LED Monitor with speakers

- 24" LED display
- Full HD resolution 1920 x 1080 pixels
- Integrated speakers
- Contrast ratio 3000:1 from the darkest blacks to the brightest whites for a more dynamic viewing experience
- Flicker free display to reduce eye fatigue
- 16.7 million display colours delivering greater colour depth
- Low blue light to help protect your eyes and keep them more comfortable during prolonged use
- HDMI, VGA and PC audio connections

**Product Description:**

This Cello 24" LED monitor is elegantly designed for use in an office or home environment. The Full HD display delivers 16.7 million colours for greater colour depth as well as high dynamic contrast at 3000:1. For prolonged use, the operators eyes are protected and comforted via the flicker free display and its low blue light output.

This Cello monitor also includes built-in speakers for added convenience and ease-of-use. The product comes complete with VGA cable and power cord.

	EAN	5060062268515
<b>Panel Specifications</b>	Size	23.8" diagonal
	Panel	FHD VA AUO
	Display scale	16:9
	Backlight	ELED edge Type
	Maximum resolution	1920 x 1080
	Best working resolution	1920 x 1080 @ 60Hz
	Pixel Pitch	0.2745mm (H) x 0.2745mm (V)
	Active Area	527.04mm x 296.46mm
	Viewing angle	H:178°, V:178° (CR>10)
	Center Luminance of White	Min:200cd/m <sup>2</sup> ; Typ:250cd/m <sup>2</sup>
	Contrast ratio	Typ:3000:1
	Response time	Typ:5ms
	Display Colours	16.7 M
	Colour Gamut	Typ:72%

<b>Display resolution</b>	Input Signal	Mode	Resolution	Refresh rate	
	VGA	VGA	VGA	640 x 480	60HZ
		SVGA	SVGA	800 x 600	60HZ
		XGA	XGA	1024 x 768	60HZ
		SXGA	SXGA	1280 x 1024	60HZ
		WXGA	WXGA	1440 x 900	60HZ
		WUXGA	WUXGA	1920 x 1080	60HZ

<b>Interface configuration</b>	Input Interface	HDMI	1
		VGA	1
		PC-Audio	1

<b>Structure size</b>	Base	BASE	BCE2-24
		Elevation adjustment	Supported
	Size:	product size(without base)	550 x 324.5 x 31.6mm (Thinnest:8.5mm)
		product size(with base)	550 x 388 x 131mm
		Packing size	620 x 470 x 100mm
Weight	With BCE2-24: Net weight 2.8Kg; Gross weight: 3.75Kg		

<b>Power management</b>	Power (DC Power Adapter)	DC 12V/3A
	Working consumption	≤36W
	Standby consumption	≤0.5W
	Speaker	2 x 2W

<b>Special Functions</b>	Flicker Free	Supported
	Low blue light	Supported

<b>Safety &amp; certification</b>	Authentication		CE
	Environment	Working condition	Temperature: 5°C~40°C humidity: 10%~85% atmosphere: 86kPa~104kPa
		Storage condition	Temperature: -20°C~55°C humidity: 5%~95% atmosphere: 86kPa~104kPa

<b>Accessory</b>	LED Monitor	1PCS
	Base	1PCS
	Instructions	1PCS
	VGA Cable	1PCS
	Power Adaptor	1PCS